

Internal vibrator

3

BRECON Intenal vibrators PROFI LINE 200 Hz, 42 V or 250 V



Type	Head diameter [mm]	Head lenght [mm]	Nominal current [A]	Voltage [V]	200 Hz, 12.000 1/min	Power [kW]	Weight [kg]
18 031 001	31	330	10,00	42		200 Hz, 12.000 1/min	0,75
18 038 601*	38	310	4,00	42	0,27		10,0
18 050 601*	50	360	10,00	42	0,60		14,5
18 058 601*	58	370	14,00	42	0,83		16,0
18 065 601*	65	380	18,00	42	1,10		20,0
18 080 001	80	450	55,00	42	4,00		30,0
18 031 003	31	330	1,70	250	200 Hz, 12.000 1/min	0,75	10,0
18 038 603*	38	310	1,00	250		0,27	10,0
18 050 603*	50	360	2,00	250		0,60	14,5
18 058 603*	58	370	2,50	250		0,83	16,0
18 065 603*	65	380	3,00	250		1,10	20,0
18 080 003	80	450	9,30	250		4,00	30,0

with 5 m hose, 15 m power cable, CEE plug and switch

*Also available with vulkollan cap on request at extra costs (please indicate when ordering)

ATTENTION: for comparison with other internal vibrator manufacturers, the indicated current is for the no-load condition (i. e. vibrator head hanging vertically and operating in free air). Under full-load conditions (i. e. vibrator head fully submersed in no-slump concrete), the current can be double the no-load current.

BRECON Spade grip pokers PROFI LINE 200 Hz, 42 V



Type	Head diameter [mm]	Head lenght [mm]	Nominal current [A]	Voltage [V]	200 Hz, 12.000 1/min	Power [kW]	Weight [kg]
18 031 005	31	330	10,00	42		200 Hz, 12.000 1/min	0,75
18 038 605*	38	310	4,00	42	0,27		9,0
18 050 605*	50	360	10,00	42	0,60		13,0
18 058 605*	58	370	14,00	42	0,83		14,0
18 065 605*	65	380	18,00	42	1,10		18,0

with 1 m hose, 15 m power cable, CEE plug and switch

*Also available with vulkollan cap on request at extra costs (please indicate when ordering)

ATTENTION: for comparison with other internal vibrator manufacturers, the indicated current is for the no-load condition (i. e. vibrator head hanging vertically and operating in free air). Under full-load conditions (i. e. vibrator head fully submersed in no-slump concrete), the current can be double the no-load current.